

## COMETEO □□□□□□□□□□□□□□

□□: F8900



□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□:

- □□□□□□□□□□□□□□
- □□□□□□□□/□□□□
- □□□□□□□□□□□□□□.
- □□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□210mm□□□□□□□□□□□□□□□□

□□□□ASA□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□

### □□□□

GENERAL TECHNICAL DATA	
Supply voltage	12 Vdc
Power consumption of fan	0.6 W
Pulse output	2 pulse / rev. (max. current of output is < 5 mA, the pulse output is not protected against short circuits)
Temperature operating range	-40 to +80 °C
Relative humidity operating range	0 to 100 %RH
Storage temperature range	-40 to +80 °C
Storage relative humidity range	0 to 100 %RH (no condensation)
Dimension	220 mm (diameter), 250 mm (height)
Weight	approx. 900 g
Material	ASA - UV stabilized, antistatic
Warranty	3 years