

H3060 230Vac/8A

Model: H3060

Product description and specifications



Table

Power supply	250Vac, 8A
Power	100W - 150W
Humidity	0 to 100%
Humidity accuracy	±2.5% RH (5 to 95% at 23°C)
Temperature	±0.4°C
Temperature accuracy	±0.1°C
Temperature range	±1.5°C (T < 25°C) RH > 30% RH -60 to +80 °C
Humidity range	±1.5g/m ³ (T < 25°C) RH 0 to 400 g/m ³
Humidity accuracy	±2g/kg (T < 35°C) RH 0 to 550 g/kg
Humidity accuracy	±2g/kg (T < 35°C) RH 0 to 995 g/kg
Humidity accuracy	±3kJ/kg (T < 25°C) RH: 0 to 995 kJ/kg
Temperature range	-30 to +80°C
LCD display	Backlight +70°C, LCD +70°C, LCD
Display	Backlight
Display accuracy	0.025mm - 0.05mm
IP rating	IP65 (indoor), IP40 (outdoor)
Voltage	110 to 240V / 50Hz to 60Hz
Current	230 VAC - 70 mA, 115 VAC - 120 mA
Dimensions	136 x 214 x 45 mm (W x H x D), 75mm
Weight	390g
Warranty	3 years