

# H3060 230Vac/8A

Model: H3060

Product description and specifications



Table

Power supply	250Vac, 8A
Dimensions	mm - mm
Humidity range	0 to 100%
Humidity accuracy	±2.5% RH 5 to 95% at 23°C
Temperature accuracy	±0.4°C
Temperature range	mm
Temperature accuracy	±1.5°C (T < 25°C) RH > 30% RH -60 to +80 °C
Humidity accuracy	±1.5g/m3 (T < 25°C) RH 0 to 400 g/m3
Humidity accuracy	±2g/kg (T < 35°C) RH 0 to 550 g/kg
Humidity accuracy	±2g/kg (T < 35°C) RH 0 to 995 g/kg
Humidity accuracy	±3kJ/kg (T < 25°C) RH: 0 to 995 kJ/kg
Temperature range	-30 to +80°C
LCD display	mm +70°C mm +70°C LCD
Resolution	mm
Resolution	0.025mm - mm
IP rating	IP65 mm, IP40 mm
Voltage	110 to 240V / 50Hz to 60Hz
Current	230 VAC - mm 70 mA, 115 VAC - mm 120 mA
Dimensions	136 x 214 x 45 mm (W x H x D), mm 75mm
Weight	mm 390g
Material	3