

H3061P 230Vac/8A

Model: H3061P

Temperature + RH sensor, 25 bar, 1, 2 or 4 channels



Table

Power supply	250Vac, 8A
Output	4 channels - 12 bit
Humidity range	0 to 100%
Humidity accuracy	±2.5% RH (0 to 95% at 23°C)
Temperature range	±0.4°C (-30 to +100°C) / ±0.4% from reading over +100°C
Temperature accuracy	±0.4°C
Temperature range	-30 to +80°C
Temperature accuracy	±1.5°C (-30 to +10°C) / ±2.5°C (+10 to +25°C)
Temperature accuracy	±2.0°C (+10 to +25°C)
Temperature accuracy	±3.0°C (-10 to +25°C)
Temperature accuracy	±6.0°C (-20 to +25°C)
Humidity accuracy	±1.5g/m ³ (T < 25°C) / ±0 to 400 g/m ³
Humidity accuracy	±2g/kg (T < 35°C) / ±0 to 550 g/kg
Humidity accuracy	±2g/kg (T < 35°C) / ±0 to 995 g/kg
Humidity accuracy	±3kJ/kg (T < 25°C) / ±0 to 995 kJ/kg
Temperature range	-30 to +80°C
LCD display	128 x 64 pixels, +70°C, -70°C, LCD
Temperature range	-30 to +125°C
Humidity range	0.025mm - 100mm
IP rating	IP65 (front), IP40 (back)
Voltage	110 to 240V / 50Hz to 60Hz
Current	230 VAC - max 70 mA, 115 VAC - max 120 mA
Dimensions	G1/2" O-ring
Dimensions	1m, 2m or 4m cable
Weight	136 x 161 x 45 mm (W x H x D), depth 150 mm, hole 18mm
Weight	max 490g - 1m cable
Weight	3kg