

H3061P 230Vac/8A

Model: H3061P

Temperature and Humidity sensor
 bar 1 or 2 or 4
 ...



...

| | |
|---------|---|
| ... | 250Vac, 8A |
| ... | ... |
| ... | 0 to 100% |
| ... | ±2.5% ... 5 to 95% at 23°C |
| ... | ±0.4°C -30 to +100°C ±0.4% from reading over +100°C |
| ... | ... |
| ... | -30 to +80°C |
| ... | 1.5°C ... +10°C ... +25°C |
| ... | 2.0°C ... +0°C ... +25°C |
| ... | 3.0°C ... -10°C ... +25°C |
| ... | 6.0°C ... -20°C ... +25°C |
| ... | ±1.5g/m ³ ... T < 25°C ... 0 to 400 g/m ³ |
| ... | ±2g/kg ... T < 35°C ... 0 to 550 g/kg |
| ... | ±2g/kg ... T < 35°C ... 0 to 995 g/kg |
| ... | ±3kJ/kg ... T < 25°C ... 0 to 995 kJ/kg |
| ... | -30 to +80°C |
| LCD ... | ... +70°C ... +70°C ... LCD |
| ... | -30 to +125°C |
| ... | 0.025mm - ... |
| IP ... | IP65 ... , IP40 ... |
| ... | 110 to 240V / 50Hz to 60Hz |
| ... | 230 VAC - ... 70 mA, 115 VAC - ... 120 mA |
| ... | G1/2" O ... |
| ... | 1m, 2m or 4m ... |
| ... | 136 x 161 x 45 mm (W x H x D), ... 150 mm, ... 18mm |
| ... | ... 490g - 1m ... |

