

H3061P-2 230Vac/8A - kopie

Model: H3061P-2

Temperature and Humidity (T+RH) sensor, 25 bar, 1, 2, 4 channels



Table

Power supply	250Vac, 8A
Channels	1 - 4
Humidity range	0 to 100%
Humidity accuracy	±2.5% RH (5 to 95% at 23°C)
Temperature range	±0.4°C (-30 to +100°C) / ±0.4% from reading over +100°C
Temperature accuracy	±0.4°C
Temperature range	-30 to +80°C
Temperature accuracy	1.5°C (0 to +10°C) / ±0.4°C (+10 to +25°C)
Temperature accuracy	2.0°C (0 to +0°C) / ±0.4°C (+25 to +50°C)
Temperature accuracy	3.0°C (0 to -10°C) / ±0.4°C (+25 to +50°C)
Temperature accuracy	6.0°C (0 to -20°C) / ±0.4°C (+25 to +50°C)
Humidity accuracy	±1.5g/m ³ (T < 25°C) / ±0.4g/m ³ (0 to 400 g/m ³)
Humidity accuracy	±2g/kg (T < 35°C) / ±0.4g/kg (0 to 550 g/kg)
Humidity accuracy	±2g/kg (T < 35°C) / ±0.4g/kg (0 to 995 g/kg)
Humidity accuracy	±3kJ/kg (T < 25°C) / ±0.4kJ/kg (0 to 995 kJ/kg)
Temperature range	-30 to +80°C
LCD display	16x2 characters, +70°C, +70°C, LCD
Operating temperature	-30 to +125°C
Probe diameter	0.025mm - 0.05mm
IP rating	IP65 (probe), IP40 (unit)
Voltage	110 to 240V / 50Hz to 60Hz
Current	230 VAC - 70 mA, 115 VAC - 120 mA
Mounting	G1/2" O-ring
Dimensions	1m, 2m or 4m cable
Weight	136 x 161 x 45 mm (W x H x D), 150 mm, 18mm
Weight	490g - 1m cable

