

H3531R - 0000000000000000000000000000 - kopie - kopie

00: H3531R-4



000000000020000000
 H3531R000000000000000000000000000000030000000000002000000000000
 000
 000
 000000

0000

00000000	0 to 100%
00000000	±2.5%000005 to 95% at 23°C
0000000	±0.4°C
000	0.1°C, 0.1%RH
0000	2s
0000000	00000000
000	000000000000000000000000
000000000000	±1.5°C00000T<25°C RH>30% 00 -60 to +80 °C
000000000000	±1.5g/m300000 T < 25°C 00 0 to 400 g/m3
000000000000	±2g/kg000000 T < 35°C 00 0 to 550 g/kg
000000000000	±2g/kg000000 T < 35°C 00 0 to 995 g/kg
000000000000	±3kj/kg000000 T < 25°C 00: 0 to 995 kj/kg
Temperature compensation of the humidity sensor	all temperature range
0000000	-30 to +80°C
IP00000	IP30
00000000	2
000000000000000000000000	50V, 2A, 60VA
0000000000	3
00000000	00000000000000000 00000000
00000000000000	500ms
000000	0 to +0.5V
000000	+3.0 to +30V
0000	00000000 - 000
LAN00	RJ-450000010Base-T00100Base-TX
0000	WWW, ModbusTCP, SNMPv1, SOAP
0000	E-mail (00SMTP00)0SNMP Trap0Syslog
00000000	T-Sensor, Telnet, keyboard

LCD	+70°C +70°C LCD
	0.025mm -
	12Vdc, 1W
	co-axial, 5.5 x 2.1mm
	1m, 2m or 4m
	483 x 44 x 45 mm (W x H x D), 19
	1090g - 1
	3