

H6020 CO2 2

Model: H6020

CO2, RH, CO2 2



Table

Power supply	50V, 2A, 60VA
Dimensions	136 x 213 x 45 mm
CO2 range	0 to 2000ppm
CO2 accuracy	±(50ppm +2%) at 25°C and 1013hPa
CO2 range	0 to 10000ppm ±(100ppm +5%) at 25°C and 1013hPa
CO2 accuracy	±2.5% RH 5 to 95% at 23°C
CO2 accuracy	±0.4°C
CO2 accuracy	±0.0001t
CO2 accuracy	±1.5°C RH>30% -60 to +80 °C
CO2 accuracy	±1.5g/m3 T < 25°C 0 to 400 g/m3
CO2 accuracy	±2g/kg T < 35°C 0 to 550 g/kg
CO2 accuracy	±2g/kg T < 35°C 0 to 995 g/kg
CO2 accuracy	±3kJ/kg T < 25°C 0 to 995 kJ/kg
CO2 response time	15s
CO2 range	-30 to +60°C
CO2 accuracy	0.025mm - 0.05mm
IP rating	IP30, IP40
Power	9-30Vdc, 1W
Dimensions	136 x 213 x 45 mm (W x H x D), 75 mm
Weight	360g
Life span	3 years