

H7530



Model: H7530

Weather station with 2 sensors

H7530 weather station with 3 sensors and 2 sensors

...

...

...

...

Humidity	0 to 100%
Humidity accuracy	±2.5% RH (5 to 95% at 23°C)
Temperature	±0.4°C
Pressure	600 to 1100hPa
Pressure accuracy	±1.3hPa at 23°C
Resolution	0.1°C, 0.1%RH, 0.1hPa
Response time	2s
Display	...
Units	hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2
Operating temperature	±1.5°C (T < 25°C) RH > 30% -60 to +80 °C
Operating humidity	±1.5g/m3 (T < 25°C) 0 to 400 g/m3
Operating weight	±2g/kg (T < 35°C) 0 to 550 g/kg
Operating energy	±2g/kg (T < 35°C) 0 to 995 g/kg
Operating power	±3kJ/kg (T < 25°C) 0 to 995 kJ/kg
Storage temperature	...
Storage humidity	-30 to +80°C
IP rating	IP40
Power consumption	2
Power supply	50V, 2A, 60VA
Power factor	3
Power mode	...
Power delay	500 ms
Power range	0 to +0.5 V
Power range	+3.0 to +30V
Power range	...
LAN	RJ-45 10Base-T 100Base-TX

□□□□	WWW, ModbusTCP, SNMPv1, SOAP
□□□□	E-mail (□□SMTP□□)□SNMP Trap□Syslog
□□□□□□□	T-Sensor, Telnet, keyboard
LCD□□□□□□□□□□	□□□□□□+70°C□□□□+70°C□□□□LCD□□□□
□□	9-30Vdc, □□□□ 1W
□□□□	□□□□, □□5.5 x 2.1mm
□□	136 x 213 x 45 mm (W x H x D), □□75 mm
□□	□□360g
□□	3□