

P8641 POE -

Model: P8641



POE

Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

Table

DSTR162/C, DSTGL40/C, DSTG8/C	$\pm 0.5^{\circ}\text{C}$ from -10 to $+80^{\circ}\text{C}$, else $\pm 2^{\circ}\text{C}$
DSRH01, DSRH02, DSRH05	$\pm 3.5\%$ RH (10% - 90% RH) at 25°C , $\pm 2^{\circ}\text{C}$
DSTR162/C, DSTGL40/C	-30 to $+80^{\circ}\text{C}$
DSTG8/C	-50 to $+100^{\circ}\text{C}$
DSRH01, DSRH02, DSRH05	0 to 100%RH (not condensing)
DSRH01, DSRH02, DSRH05	0 to $+50^{\circ}\text{C}$
Resolution	0.1°C , 0.1% RH
Response time	2s
Power supply	POE
Operating temperature	-20 to $+60^{\circ}\text{C}$
IP protection	IP30
LAN	RJ-45 10Base-T 100Base-TX
Protocols	WWW, ModbusTCP, SNMPv1, SOAP
Alerts	E-mail (SMTP) SNMP Trap Syslog
Outputs	T-Sensor, WWW
Power consumption	POE IEEE 802.3af 5Vdc
Dimensions	88 x 74 x 39.5 mm
Weight	140g
Quantity	3