

P8652 P-line POE - 3-Port PoE Switch

Model: P8652



P-line (POE) switch, 3-port PoE switch, 3-port PoE switch, 3-port PoE switch

Table

| | |
|-------------------------------|---------------------------------------|
| DSTR162/C, DSTGL40/C, DSTG8/C | ±0.5°C from -10 to +80°C, else ±2°C |
| DSRH01, DSRH02, DSRH05 | ±3.5% RH (10% - 90% RH) at 25°C, ±2°C |
| DSTR162/C, DSTGL40/C | -30 to +80°C |
| DSTG8/C | -50 to +100°C |
| DSRH01, DSRH02, DSRH05 | 0 to 100%RH (not condensing) |
| DSRH01, DSRH02, DSRH05 | 0 to +50°C |
| Temp | 0.1°C, 0.1%RH |
| Response | 2s |
| Protocol | Modbus RTU, Modbus TCP |
| IP | IP30 |
| Port | 3 |
| Port | 3 |
| Port | 3 |
| LAN | RJ-45 10Base-T/100Base-TX |
| Protocol | WWW, ModbusTCP, SNMPv1, SOAP |
| Protocol | E-mail (SMTP), SNMP Trap, Syslog |
| Protocol | T-Sensor, WWW |
| Power | POE IEEE 802.3af 5Vdc |
| Size | 5.5 x 2.1 mm |
| Size | 88 x 74 x 39.5 mm (W x H x D) |
| Weight | 145g |
| Port | 3 |