

P8652 P-line POE - 3-Port

Model: P8652



P-line (POE) device, 3-port RJ45 ports, 3-year warranty

Table

DSTR162/C, DSTGL40/C, DSTG8/C	±0.5°C from -10 to +80°C, else ±2°C
DSRH01, DSRH02, DSRH05	±3.5% RH (10% - 90% RH) at 25°C, ±2°C
DSTR162/C, DSTGL40/C	-30 to +80°C
DSTG8/C	-50 to +100°C
DSRH01, DSRH02, DSRH05	0 to 100%RH (not condensing)
DSRH01, DSRH02, DSRH05	0 to +50°C
Resolution	0.1°C, 0.1%RH
Response time	2s
Accuracy	±0.5°C, ±0.5%RH
IP Rating	IP30
Ports	3
Mounting	Panel
Mounting holes	4x Ø4mm
LAN	RJ-45 10Base-T/100Base-TX
Protocols	WWW, ModbusTCP, SNMPv1, SOAP
Alerts	E-mail (SMTP), SNMP Trap, Syslog
Alerts	T-Sensor, WWW
Power	POE IEEE 802.3af 5Vdc
Dimensions	5.5 x 2.1 mm
Weight	88 x 74 x 39.5 mm (W x H x D)
Weight	145g
Warranty	3 years