

# P8652 P-line POE - 3-Port PoE Switch

Model: P8652



P-line (POE) switch, 3-port PoE switch, 3-port PoE switch

Table

DSTR162/C, DSTGL40/C, DSTG8/C	±0.5°C from -10 to +80°C, else ±2°C
DSRH01, DSRH02, DSRH05	±3.5% RH (10% - 90% RH) at 25°C, ±2°C
DSTR162/C, DSTGL40/C	-30 to +80°C
DSTG8/C	-50 to +100°C
DSRH01, DSRH02, DSRH05	0 to 100%RH (not condensing)
DSRH01, DSRH02, DSRH05	0 to +50°C
Temp	0.1°C, 0.1%RH
Response	2s
Protocol	Modbus RTU, Modbus TCP
IP	IP30
Port	3
Port	1
Port	10/100Base-T
LAN	RJ-45 10Base-T/100Base-TX
Protocol	WWW, ModbusTCP, SNMPv1, SOAP
Protocol	E-mail (SMTP), SNMP Trap, Syslog
Protocol	T-Sensor, WWW
Power	POE IEEE 802.3af 5Vdc
Size	5.5 x 2.1 mm
Size	88 x 74 x 39.5 mm (W x H x D)
Weight	145g
Port	3