

# P8652 POE - - kopie

№: P8653

P-line (POE) , , 3



№№

TEMPERATURE SENSOR	
Measuring range	-55 to +105 °C
Accuracy	according to the connected probe DSxx
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	according to the connected probe DSxx
Accuracy	according to the connected probe DSxx
Resolution	0.1% RH
FLOOD DETECTOR	
Usage	Intended for indoor usage only
Cable length	2.5 meters (can't be extended)
Two wire connection	red wire - active, black wire - GND, directly powered from P8653
BINARY INPUT	
Parameters of the voltage contact	Voltage input level for „L“:< 1,0 V; Voltage input level for „H“:> 2,5 V; Internal resistivity of the voltage source < 2kOhm Input voltage range 0 to +30 V
Parameters of the voltage-free contact	Voltage on the unclosed contact 3,3 V Current through closed contact 0,1 mA Maximum resistivity of the contact < 5kOhm
GENERAL TECHNICAL DATA	
Operating temperature	-20 to +60 °C
Channels	1x external temperature probe nebo 1x connectable temperature+humidity probe
Output	Ethernet
Measuring interval	2 s
Available temperature units	degrees Celsius, degrees Fahrenheit
Communication protocol	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alarm protocols	E-mail, SNMP Trap, Syslog

Power	Power over Ethernet according to IEEE 802.3af or 5Vdc
Protection class	IP30
Dimensions	88 x 74 x 39,5 mm
Weight	approx. 125 g
Warranty	3 years