

S6021 - 0-20mA, 0-20V

Model: S6021



Features:
 - 2000 counts
 - 1000 levels
 - 500 ms (auto)
 - 0.5 Hz (10s)
 - 3 uA (auto)
 - 3.6 V
 - 0 to +0.2 V (3 uA)
 - +3.0 to +30 V (100 nA)
 - D-Sub 9, 4-pin
 - 10s/24h
 - 10%/1000
 - 1000 - 1000000
 - 1000 - 1000000
 - 1000 - 1000000
 - IP67 - 93x64x29mm
 - 130g
 - 30

Connectivity: USB, COM, RS232, GSM

Table:

Operating Temperature	-30°C +70°C
Accuracy	±0.2% FS
Resolution	7900 levels
Count	2000
Update Rate	500 ms (auto)
Filter	0.5 Hz (10s)
Current	3 uA (auto)
Voltage	3.6 V
Current Range	0 to +0.2 V (3 uA)
Voltage Range	+3.0 to +30 V (100 nA)
Interface	D-Sub 9, 4-pin
Response Time	10s/24h
Accuracy	10%/1000
Range	1000 - 1000000
Power	AA 3.6V
Resolution	6
Resolution	4
Resolution	1
IP Rating	IP67 - 93x64x29mm
Weight	130g
Dimensions	30