

Pt1000TR160/E, 1000, 10, ELKA

Code: SN199E



IP protection (IP67) and operating temperature range: -30°C to +80°C.

Accuracy: $t = \pm(0.30 + 0.005 \cdot |t|)$ - class B according to IEC 751.

Material: 100% PVC jacketed

Dimensions: 6mm diameter, 20mm length. Cable diameter: 3.5mm. ELKA connector.

Table

| | |
|-------------------------|----------------------------------------------------------------------------------------------------|
| TEMPERATURE SENSOR | |
| Measuring range | -30 to +80 °C |
| Accuracy | $\pm (0.3 + 0.005 t)$ at °C |
| Accuracy class | A |
| Time response | $t_{0.5} < 12$ s (in flowing water at > 0.2 m/s) $t_{50} < 12$ s, $t_{90} < 32$ s (in liquid) |
| Type of sensing element | Pt1000 |
| Temperature coefficient | 3850 ppm / °C |
| GENERAL TECHNICAL DATA | |
| Wire connection | 2-wire connection |
| Material of the case | POLYAMIDE-based plastic |
| Dimensions of the case | length 20 mm; diameter 5.7 ± 0.1 mm |
| Lead-in cable | PVC shielded |
| Length of lead-in cable | 1 meter |
| Connector | ELKA |
| IP protection | IP67 |
| Warranty | 30 months |