

# T0210 0-10V



Model: T0210

Temperature and Humidity

Temperature: ±0.4°C, Humidity: ±2.5%

NEW - AC Power - 24 Vac !

Table

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH (5 to 95% at 23°C)
Temperature Accuracy	±0.4°C
Temperature Range	-60 to +80 °C
Temperature Accuracy (RH > 30%)	±1.5°C (T < 25°C)
Humidity Accuracy (T < 25°C)	±1.5g/m <sup>3</sup> (0 to 400 g/m <sup>3</sup> )
Humidity Accuracy (T < 35°C)	±2g/kg (0 to 550 g/kg)
Humidity Accuracy (T < 35°C)	±2g/kg (0 to 995 g/kg)
Humidity Accuracy (T < 25°C)	±3kJ/kg (0 to 995 kJ/kg)
Temperature Range	-30 to +80°C
Humidity Range	0-100%
Temperature Range	0-10V
Humidity Range	0.025mm - 100mm
IP Rating	IP65 (front) IP40 (back)
Power	15-30Vdc @ 20mA; 24Vac
Dimensions	88.5 x 170 x 39.5 mm (W x H x D), 75 mm
Weight	150g
Warranty	3 years