

# T0211 0-10V

Model: T0211

Temperature and Humidity / Moisture  
 Temperature and Humidity and Moisture

NEW - AC Power - 24 Vac !



Table

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH (5 to 95% at 23°C)
Temperature	±0.4°C from -30 to +100°C ±0.4% (over +100°C)
Temperature Accuracy	±1.5°C (T < 25°C, RH > 30%) -60 to +80 °C
Moisture	±1.5g/m <sup>3</sup> (T < 25°C) 0 to 400 g/m <sup>3</sup>
Moisture Accuracy	±2g/kg (T < 35°C) 0 to 550 g/kg
Moisture Accuracy	±2g/kg (T < 35°C) 0 to 995 g/kg
Moisture Accuracy	±3kJ/kg (T < 25°C) 0 to 995 kJ/kg
Temperature Range	-30 to +80°C
LCD Display	Backlight +70°C, LCD
Power	0-10V
Power Accuracy	0.025mm - PC
IP Rating	IP65 / IP40
Power	15-30Vdc @ 20mA; 24Vac
Power	1m, 2m, 4m
Power	88.5 x 170 x 39.5 mm (W x H x D), 88 mm, 18 mm
Power	210g
Power	3