

T0211 0-10V - kopie

Model: T0211-2

Temperature and Humidity

Temperature range: -30 to +100°C



NEW - AC Power - 24 Vac !

Table

| | |
|----------------------|--|
| Humidity | 0 to 100% |
| Humidity Accuracy | ±2.5% RH (5 to 95% at 23°C) |
| Temperature Accuracy | ±0.4°C from -30 to +100°C ±0.4% (over +100°C) |
| Temperature Range | -60 to +80 °C |
| Temperature Accuracy | ±1.5°C (T < 25°C, RH > 30%) -60 to +80 °C |
| Humidity Accuracy | ±1.5g/m ³ (T < 25°C) 0 to 400 g/m ³ |
| Humidity Accuracy | ±2g/kg (T < 35°C) 0 to 550 g/kg |
| Humidity Accuracy | ±2g/kg (T < 35°C) 0 to 995 g/kg |
| Humidity Accuracy | ±3kJ/kg (T < 25°C) 0 to 995 kJ/kg |
| Temperature Range | -30 to +80°C |
| LCD Display | Backlight +70°C, LCD |
| Power | 0-10V |
| Power | PC |
| Power | 0.025mm - |
| IP Rating | IP65, IP40 |
| Power | 15-30Vdc, 20mA; 24Vac |
| Power | 1m, 2m, 4m |
| Dimensions | 88.5 x 170 x 39.5 mm (W x H x D), 88 mm, 18 mm |
| Weight | 210g |
| Quantity | 3 |