

T0211P 0-10V

Model: T0211P

25bar 1 2 4



NEW - AC Power - 24 Vac !

Table

Accuracy	0 to 100%
Resolution	±2.5% 5 to 95% at 23°C
Linearity	±0.4°C -30 to +100°C / ±0.4% from reading over +100°C
Temperature range	-60 to +80°C
Temperature range	1.5°C +10°C to +25°C
Temperature range	2.0°C +0°C to +25°C
Temperature range	3.0°C -10°C to +25°C
Temperature range	6.0°C -20°C to +25°C
Humidity range	±1.5g/m ³ T < 25°C 0 to 400 g/m ³
Humidity range	±2g/kg T < 35°C 0 to 550 g/kg
Humidity range	±2g/kg T < 35°C 0 to 995 g/kg
Humidity range	±3kJ/kg T < 25°C 0 to 995 kJ/kg
Temperature range	-30 to +80°C
LCD display	+70°C +70°C LCD
Power supply	0-10V
Power supply	0.025mm
IP rating	IP65, IP40
Power supply	15-30Vdc, 20mA, 24Vac
Power supply	G1/2"
Power supply	1m, 2m or 4m
Dimensions	88.5 x 114 x 39.5 mm (W x H x D), 150 mm, 18mm
Weight	260g
Weight	3