

T0211P 0-10V

Model: T0211P

25bar 1 2 4



NEW - AC Power - 24 Vac !

Table

Accuracy	0 to 100%
Resolution	±2.5% 5 to 95% at 23°C
Temperature	±0.4°C -30 to +100°C ±0.4% from reading over +100°C
Humidity	0 to 100%
Temperature range	-60 to +80°C
Temperature accuracy	1.5°C 10°C to +25°C
Temperature accuracy	2.0°C 0°C to +25°C
Temperature accuracy	3.0°C -10°C to +25°C
Temperature accuracy	6.0°C -20°C to +25°C
Moisture accuracy	±1.5g/m ³ T < 25°C 0 to 400 g/m ³
Moisture accuracy	±2g/kg T < 35°C 0 to 550 g/kg
Moisture accuracy	±2g/kg T < 35°C 0 to 995 g/kg
Moisture accuracy	±3kJ/kg T < 25°C 0 to 995 kJ/kg
Temperature range	-30 to +80°C
LCD display	0 to 100% +70°C LCD
Power supply	0-10V
Power supply	0.025mm -
IP rating	IP65, IP40
Power supply	15-30Vdc, 20mA, 24Vac
Power supply	G1/2"
Power supply	1m, 2m or 4m
Power supply	88.5 x 114 x 39.5 mm (W x H x D), 150 mm, 18mm
Power supply	260g
Power supply	3