

T0211P 0-10V - kopie

Model: T0211P-2

Pressure range: 0-25 bar, Accuracy: ±0.4% (0-100°C), ±0.4% (100-200°C), ±0.4% (200-400°C)

NEW - AC Power - 24 Vac !



Table

| | |
|----------|---|
| Accuracy | 0 to 100% |
| Accuracy | ±2.5% (0 to 95% at 23°C) |
| Accuracy | ±0.4°C (-30 to +100°C) / ±0.4% from reading over +100°C |
| Accuracy | ±0.4% |
| Accuracy | -60 to +80°C |
| Accuracy | 1.5°C (0 to +10°C) / ±0.4% (+25 to +100°C) |
| Accuracy | 2.0°C (0 to +0°C) / ±0.4% (+25 to +100°C) |
| Accuracy | 3.0°C (0 to -10°C) / ±0.4% (+25 to +100°C) |
| Accuracy | 6.0°C (0 to -20°C) / ±0.4% (+25 to +100°C) |
| Accuracy | ±1.5g/m ³ (T < 25°C) / 0 to 400 g/m ³ |
| Accuracy | ±2g/kg (T < 35°C) / 0 to 550 g/kg |
| Accuracy | ±2g/kg (T < 35°C) / 0 to 995 g/kg |
| Accuracy | ±3kJ/kg (T < 25°C) / 0 to 995 kJ/kg |
| Accuracy | -30 to +80°C |
| LCD | 0 to +70°C / 0 to +70°C / LCD |
| Accuracy | ±0.4% |
| Accuracy | 0-10V, 0-10V |
| Accuracy | ±0.4% |
| Accuracy | 0.025mm - 0.025mm |
| IP | IP65, IP40 |
| Accuracy | 15-30Vdc, 20mA, 24Vac |
| Accuracy | G1/2" |
| Accuracy | 1m, 2m or 4m |
| Accuracy | 88.5 x 114 x 39.5 mm (W x H x D), 150 mm, 18mm |
| Accuracy | ±260g |
| Accuracy | 3" |