

T0211P 0-10V - kopie

Model: T0211P-2

Pressure range: 0-25 bar, Accuracy: ±0.4% (0-100°C), ±0.4% (100-200°C), ±0.4% (200-400°C)

NEW - AC Power - 24 Vac !



Table

Accuracy	0 to 100%
Accuracy	±2.5% (0 to 95% at 23°C)
Accuracy	±0.4°C (-30 to +100°C) / ±0.4% from reading over +100°C
Accuracy	±0.4%
Accuracy	-60 to +80°C
Accuracy	1.5°C (0 to +10°C) / ±0.4% (+25 to +100°C)
Accuracy	2.0°C (0 to +0°C) / ±0.4% (+25 to +100°C)
Accuracy	3.0°C (0 to -10°C) / ±0.4% (+25 to +100°C)
Accuracy	6.0°C (0 to -20°C) / ±0.4% (+25 to +100°C)
Accuracy	±1.5g/m ³ (T < 25°C) / 0 to 400 g/m ³
Accuracy	±2g/kg (T < 35°C) / 0 to 550 g/kg
Accuracy	±2g/kg (T < 35°C) / 0 to 995 g/kg
Accuracy	±3kJ/kg (T < 25°C) / 0 to 995 kJ/kg
Accuracy	-30 to +80°C
LCD	0 to +70°C / 0 to +70°C / LCD
Accuracy	±0.4%
Accuracy	0-10V, 0-10V
Accuracy	±0.4%
Accuracy	0.025mm - 0.025mm
IP	IP65, IP40
Accuracy	15-30Vdc, 20mA, 24Vac
Accuracy	G1/2"
Accuracy	1m, 2m or 4m
Accuracy	88.5 x 114 x 39.5 mm (W x H x D), 150 mm, 18mm
Accuracy	±260g
Accuracy	3"