

# T3113Ex 温湿度露点仪 4-20mA

型号: T3113Ex

ATEX认证

探头长度150mm

ATEX认证



规格

温度范围	-30~135°C
湿度范围	0 to 100%
露点范围	±2.5% RH @ 5 to 95% at 23°C
精度	±0.4°C @ -30~+100°C   ±0.4% RH @ +100°C
分辨率	0.1°C
存储温度范围	±1.5°C @ RH < 30%   -60 to +80 °C
存储湿度范围	±1.5g/m <sup>3</sup> @ T < 25°C   0 to 400 g/m <sup>3</sup>
存储露点范围	±2g/kg @ T < 35°C   0 to 550 g/kg
存储精度	±2g/kg @ T < 35°C   0 to 995 g/kg
存储分辨率	±3kJ/kg @ T < 25°C   0 to 995 kJ/kg
工作温度范围	-30 to +60°C
工作湿度范围	0 to 100%   +60°C
LCD显示	背光显示 @ +70°C   LCD显示
显示	背光显示
输出 - 类型	4-20mA, 脉冲
输出	脉冲PC
分辨率	0.025mm - 0.001mm
IP等级	IP65   IP40
电压	9-30Vdc
尺寸	88.5 x 250 x 39.5 mm (W x H x D), 150 mm
重量	225g
保修	3年