

T3319 温湿度记录仪 RS232

型号: T3319

记录器 1m, 2m, 4m 记录器
 记录器 1m 记录器



规格

湿度范围	0 to 100%
湿度精度	±2.5% RH @ 5 to 95% at 23°C
温度范围	±0.4°C @ -30 to +100°C / ±0.4% RH @ +100°C
温度精度	±0.4% RH @ +100°C
湿度精度	±0.4% RH @ +100°C
温度范围	-60 to +80 °C
湿度精度	±1.5% RH @ T < 25°C, RH > 30% / ±0.4% RH @ -60 to +80 °C
湿度精度	±1.5% RH @ T < 25°C, RH > 30% / ±0.4% RH @ -60 to +80 °C
湿度精度	±1.5g/m ³ @ T < 25°C / 0 to 400 g/m ³
湿度精度	±2g/kg @ T < 35°C / 0 to 550 g/kg
湿度精度	±2g/kg @ T < 35°C / 0 to 995 g/kg
湿度精度	±3kJ/kg @ T < 25°C / 0 to 995 kJ/kg
湿度精度	±3kJ/kg @ T < 25°C / 0 to 995 kJ/kg
湿度精度	-30 to +80°C
LCD 显示屏	单色 LCD +70°C @ +70°C 单色 LCD
湿度精度	±0.4% RH @ +100°C
湿度精度	ModBus RTU / Advantech ADAM
湿度精度	110 to 115200 Bd
湿度精度	0.025mm - 0.05mm
IP 等级	IP65 / IP40
湿度精度	9-30Vdc, 6mA
湿度精度	1m, 2m, 4m
湿度精度	88.5 x 114 x 39.5 mm (W x H x D), 88 mm, 18mm
湿度精度	290g - 1m
湿度精度	3