

T3319 温湿度记录仪 RS232

型号: T3319

记录容量: 1M, 2M, 4M
 记录间隔: 1m



规格

湿度范围	0 to 100%
湿度精度	±2.5% RH @ 5 to 95% at 23°C
温度范围	±0.4°C @ -30 to +100°C / ±0.4% RH @ +100°C
温度精度	±0.4% RH @ +100°C
湿度精度	±0.4% RH @ +100°C
温度范围	-60 to +80 °C
湿度精度	±1.5% RH @ T < 25°C, RH > 30% / ±0.4% RH @ -60 to +80 °C
湿度精度	±1.5% RH @ T < 25°C, RH > 30% / ±0.4% RH @ -60 to +80 °C
湿度精度	±1.5g/m ³ @ T < 25°C / 0 to 400 g/m ³
湿度精度	±2g/kg @ T < 35°C / 0 to 550 g/kg
湿度精度	±2g/kg @ T < 35°C / 0 to 995 g/kg
湿度精度	±3kJ/kg @ T < 25°C / 0 to 995 kJ/kg
湿度精度	±3kJ/kg @ T < 25°C / 0 to 995 kJ/kg
湿度精度	±3kJ/kg @ T < 25°C / 0 to 995 kJ/kg
LCD 显示屏	单色 LCD +70°C @ +70°C 单色 LCD
通信接口	ModBus RTU / Advantech ADAM
通信速率	110 to 115200 Bd
记录间隔	0.025mm - 1m
IP 等级	IP65 / IP40
供电电压	9-30Vdc, 最大 6mA
记录容量	1M, 2M, 4M
尺寸	88.5 x 114 x 39.5 mm (W x H x D), 厚度 88 mm, 孔径 18mm
重量	约 290g - 1m
保修	3 年