



T3319 □□□□□□□□□□□□□□□□□□□□□□□□ RS232 □□ - kopie

□□: T3319-2



□□□□□□□□□□□□□□□□□□□□□□ 1m, 2m, 4m □□□□□□□□
□□□□□□□□□□□□□□□□□□□□□□ 1m □□□□□□□□□□□□□□□□□□□□□□□□
□

□□□□

□□□□□□□□	0 to 100%
□□□□□□□□	$\pm 2.5\%$ □□□□□□ 5 to 95% at 23°C
□□□□□□□□	$\pm 0.4^{\circ}\text{C}$ □-30□+100°C $\pm 0.4\%$ □□□□□□ □+100°C □
□□□□□□□□	□□□□□□□□
□□□□□□□□	-60 to +80 °C
□□□□□□□□□□	$\pm 1.5^{\circ}\text{C}$ □□□□□□ □ T < 25°C □ RH > 30% □□ -60 to +80 °C
□□□□□□□□□□	$\pm 1.5\text{g/m}^3$ □□□□□□ □ T < 25°C □□ 0 to 400 g/m ³
□□□□□□□□□□	$\pm 2\text{g/kg}$ □□□□□□ □ T < 35°C □□ 0 to 550 g/kg
□□□□□□□□□□	$\pm 2\text{g/kg}$ □□□□□□ □ T < 35°C □□ 0 to 995 g/kg
□□□□□□□□□□	$\pm 3\text{kJ/kg}$ □□□□□□ □ T < 25°C □□ : 0 to 995 kJ/kg
□□□□□□□□	-30 to +80°C
LCD □□□□□□□□□□	□□□□□□ □+70°C □□□□ □+70°C □□□□ LCD □□□□
□□□□□□□□□□	□□□□□□□□□□
□□□□	ModBus RTU □ Advantech ADAM □□□□□□
□□□□□	110 to 115200 Bd
□□□□□□□□□□	0.025mm - □□□□□□□□
IP □□□□□	IP65 □□□□□□ IP40 □□□□
□□	9-30Vdc, □□□□□□ 6mA
□□□□□□□□	1m, 2m, 4m □□
□□	88.5 x 114 x 39.5 mm (W x H x D), □□□□ 88 mm, □□□□ 18mm
□□	□□ 290g - 1m □□□□□□
□□	3 □