

T3319 1m, 2m, 4m RS232 - kopie - kopie

Model: T3319-4



1m, 2m, 4m
1m

Table

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH @ 5 to 95% at 23°C
Temperature	±0.4°C @ -30 to +100°C / ±0.4% RH @ +100°C
Temperature Accuracy	±0.4% RH @ +100°C
Temperature Range	-60 to +80 °C
Temperature Accuracy	±1.5°C @ T < 25°C @ RH > 30% / ±0.4% RH @ -60 to +80 °C
Humidity Accuracy	±1.5g/m³ @ T < 25°C / ±0.4% RH @ 0 to 400 g/m³
Humidity Accuracy	±2g/kg @ T < 35°C / ±0.4% RH @ 0 to 550 g/kg
Humidity Accuracy	±2g/kg @ T < 35°C / ±0.4% RH @ 0 to 995 g/kg
Humidity Accuracy	±3kJ/kg @ T < 25°C / ±0.4% RH @ 0 to 995 kJ/kg
Temperature Range	-30 to +80°C
LCD Display	Monochrome +70°C @ +70°C @ LCD
Communication	ModBus RTU / Advantech ADAM
Baud Rate	110 to 115200 Bd
Probe Length	0.025mm - 1m
IP Rating	IP65 / IP40
Power	9-30Vdc, max 6mA
Dimensions	1m, 2m, 4m
Weight	88.5 x 114 x 39.5 mm (W x H x D), max 88 mm, max 18mm
Weight	±290g - 1m
Weight	3