

T3419 [Placeholder] RS485 [Placeholder] - kopie - kopie

Model: T3419-4

Accessories: [Placeholder] 1m, 2m, 4m [Placeholder]

[Placeholder] 1m [Placeholder]
[Placeholder]



[Placeholder]

[Placeholder]	0 to 100%
[Placeholder]	±2.5% [Placeholder] 5 to 95% at 23°C
[Placeholder]	±0.4°C [Placeholder] -30 to +100°C ±0.4% [Placeholder] +100°C
[Placeholder]	[Placeholder]
[Placeholder]	-60 to +80 °C
[Placeholder]	±1.5°C [Placeholder] T < 25°C [Placeholder] RH > 30% [Placeholder] -60 to +80 °C
[Placeholder]	±1.5g/m ³ [Placeholder] T < 25°C [Placeholder] 0 to 400 g/m ³
[Placeholder]	±2g/kg [Placeholder] T < 35°C [Placeholder] 0 to 550 g/kg
[Placeholder]	±2g/kg [Placeholder] T < 35°C [Placeholder] 0 to 995 g/kg
[Placeholder]	±3kJ/kg [Placeholder] T < 25°C [Placeholder]: 0 to 995 kJ/kg
[Placeholder]	-30 to +80°C
LCD [Placeholder]	[Placeholder] +70°C [Placeholder] +70°C [Placeholder] LCD [Placeholder]
[Placeholder]	[Placeholder]
[Placeholder]	ModBus RTU [Placeholder] Advantech ADAM [Placeholder]
[Placeholder]	110 to 115200 Bd
[Placeholder]	0.025mm - [Placeholder]
IP [Placeholder]	IP65 [Placeholder] IP40 [Placeholder]
[Placeholder]	9-30Vdc, [Placeholder] 0.5W
[Placeholder]	1m, 2m, 4m [Placeholder]
[Placeholder]	88.5 x 114 x 39.5 mm (W x H x D), [Placeholder] 88 mm, [Placeholder] 18mm
[Placeholder]	[Placeholder] 210g - 1m [Placeholder]
[Placeholder]	3 [Placeholder]