

T3419P 0.1% 25bar 1m, 2m, 4m RS485

Model: T3419P

Pressure range: 0.1% 25bar
 Cable lengths: 1m, 2m, 4m
 Communication: RS485



Specifications

Measurement range	0 to 100%
Accuracy	±2.5% (0 to 95% at 23°C)
Temperature range	±0.4°C (-30 to +100°C) / ±0.4% (0 to +100°C)
Temperature resolution	0.1°C
Temperature range	-60 to +80 °C
Temperature accuracy	1.5°C (-10 to +25°C)
Temperature accuracy	2.0°C (0 to +25°C)
Temperature accuracy	3.0°C (-10 to +25°C)
Temperature accuracy	6.0°C (-20 to +25°C)
Humidity range	±1.5g/m ³ (T < 25°C) / 0 to 400 g/m ³
Humidity range	±2g/kg (T < 35°C) / 0 to 550 g/kg
Humidity range	±2g/kg (T < 35°C) / 0 to 995 g/kg
Humidity range	±3kJ/kg (T < 25°C) / 0 to 995 kJ/kg
Temperature range	-30 to +80°C
LCD display	0 to +70°C / 0 to +70°C LCD
Communication	ModBus RTU / Advantech ADAM
Communication speed	110 to 115200 Bd
Cable diameter	0.025mm - 0.025mm
IP rating	IP65 / IP40
Power supply	9-30Vdc, max 0.5W
Dimensions	G1/2" O.D.
Cable length	1m, 2m, 4m
Weight	88.5 x 114 x 39.5 mm (W x H x D), max 150mm, max 18mm
Weight	max 260g - 1m cable
Quantity	3