

T3419P - kopie - kopie **RS485**

T3419P-4

25bar 1m,2m,4m
1m



Table

Pressure	0 to 100%
Accuracy	±2.5% (5 to 95% at 23°C)
Temperature	±0.4°C (-30 to +100°C) / ±0.4% (0 to +100°C)
Temperature range	Temperature
Temperature range	-60 to +80 °C
Temperature range	1.5°C (0 to +10°C) / +25°C
Temperature range	2.0°C (0 to +0°C) / +25°C
Temperature range	3.0°C (0 to -10°C) / +25°C
Temperature range	6.0°C (0 to -20°C) / +25°C
Temperature range	±1.5g/m ³ (T < 25°C) / 0 to 400 g/m ³
Temperature range	±2g/kg (T < 35°C) / 0 to 550 g/kg
Temperature range	±2g/kg (T < 35°C) / 0 to 995 g/kg
Temperature range	±3kJ/kg (T < 25°C) / 0 to 995 kJ/kg
Temperature range	-30 to +80°C
LCD display	0 to +70°C / 0 to +70°C LCD
Temperature range	Temperature
Protocol	ModBus RTU / Advantech ADAM
Speed	110 to 115200 Bd
Cable length	0.025mm -
IP rating	IP65 / IP40
Power	9-30Vdc, 0.5W
Mounting	G1/2"
Cable length	1m, 2m, 4m
Dimensions	88.5 x 114 x 39.5 mm (W x H x D), 150mm, 18mm
Weight	260g - 1m
Pages	3