

# T3511 - kopie

Model: T3511-2

Temperature and humidity sensor  
 1-wire interface

LCD display



### Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

Table

Humidity	0 to 100%
Accuracy	±2.5% RH (5 to 95% at 23°C)
Resolution	±0.4°C
Temperature	0.1°C, 0.1%RH
Response time	2s
Power supply	1-wire interface
Operating temperature	±1.5°C (T < 25°C, RH > 30%) -60 to +80°C (RH > 30%) range -60 to +80°C
Storage temperature	-30 to +80°C
IP rating	IP30, IP40
LAN	RJ-45 10Base-T, 100Base-TX
Protocols	WWW, ModbusTCP, SNMPv1, SOAP
Alerts	E-mail (SMTP), SNMP Trap, Syslog
Sensors	T-Sensor, WWW
Dimensions	0.025mm - 0.1mm
Power	9-30Vdc, 1W
Dimensions	co-axial, 5.5 x 2.1mm
Dimensions	1m, 2m or 4m
Dimensions	88.5 x 93 x 39.5mm (W x H x D), 88mm, 18mm
Weight	210g-1m
Weight	3g