

T3511P - 00000000000000000000

00: T3511P

00000000000000000000000000T+RH00000000000000000025
 bar000000000000001m,2m,4m
 00



0000

00000000	0 to 100%
00000000	±2.5%000005 to 95% at 23°C
000000	±0.4°C
000	0.1°C, 0.1%RH
0000	2s
000000	00000000
000	000000000000000000000000
000000	-60 to +80°C
00000000	1.5°C 0000+10°C000000 +25°C
00000000	2.0°C 0000+0°C000000 +25°C
00000000	3.0°C 0000-10°C000000 +25°C
00000000	6.0°C 0000-20°C000000 +25°C
000000000000	0000000000
000000	-30 to +80°C
IP0000	0000IP30,000IP40
LAN00	RJ-45000010Base-T0100Base-TX
0000	WWW, ModbusTCP, SNMPv1, SOAP
0000	E-mail (00SMTP00)0SNMP Trap0Syslog
00000000	T-Sensor,WWW00
LCD0000000000	00000000+70°C0000+70°C0000LCD0000
000000000000	0.025mm - 00000000
0000	000 00000000
00	9 to 30Vdc, 00001W
0000	co-axial, 005.5 x 2.1mm
000000	G1/20000
00000000	1m, 2m or 4m00

□□	88.5 x 93 x 39.5mm (W x H x D), □□□□ 150mm□□□□ 18mm
□□	□□260g - □□1□□□
□□	3□