

T3511P - 00000000000000000000 - kopie

00: T3511P-2

00000000000000000000000000T+RH000000000000000025
bar00000000000000001m,2m,4m
00



NO IMAGE
FOUND

Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

0000

00000000	0 to 100%
00000000	±2.5%000005 to 95% at 23°C
000000	±0.4°C
000	0.1°C, 0.1%RH
0000	2s
000000	0000000
000	00000000000000000000
000000	-60 to +80°C
00000000	1.5°C 0000+10°C00000 +25°C
00000000	2.0°C 0000+0°C00000 +25°C
00000000	3.0°C 0000-10°C000000 +25°C
00000000	6.0°C 0000-20°C00000 +25°C
0000000000	00000000
000000	-30 to +80°C
IP0000	0000IP30,000IP40
LAN00	RJ-45000010Base-T0100Base-TX
0000	WWW, ModbusTCP, SNMPv1, SOAP
0000	E-mail (00SMTP00)0SNMP Trap0Syslog
0000000	T-Sensor,WWW00
LCD0000000000	000000+70°C0000+70°C00000LCD000
0000000000	0.025mm - 000000
0000	000 000000
00	9 to 30Vdc, 00001W
0000	co-axial, 005.5 x 2.1mm
000000	G1/2"O00
0000000	1m, 2m or 4m00
00	88.5 x 93 x 39.5mm (W x H x D), 0000 150mm00000 18mm
00	00260g - 001000

