

# T3511P - XXXXXXXXXXXXXXXXXXXX - kopie - kopie

Model: T3511P-4

Measuring principle: XXXXXXXXXXXXXXXXXXXXT+RH XXXXXXXXXXXXXXXXXXXX25  
 bar XXXXXXXXXXXXXXXXXXXX1m,2m,4m  
XXXXXXXXXXXXXXXXXXXX



### Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

Table:

Humidity	0 to 100%
Accuracy	±2.5% <span style="font-family: monospace;">XXXXXXXXXXXX</span> 5 to 95% at 23°C
Resolution	±0.4°C
Temp	0.1°C, 0.1%RH
Response	2s
Measurement range	<span style="font-family: monospace;">XXXXXXXXXXXX</span>
Temp	<span style="font-family: monospace;">XXXXXXXXXXXX</span>
Measurement range	-60 to +80°C
Measurement range	1.5°C <span style="font-family: monospace;">XXXX</span> +10°C <span style="font-family: monospace;">XXXX</span> +25°C <span style="font-family: monospace;">XX</span>
Measurement range	2.0°C <span style="font-family: monospace;">XXXX</span> +0°C <span style="font-family: monospace;">XXXX</span> +25°C <span style="font-family: monospace;">XX</span>
Measurement range	3.0°C <span style="font-family: monospace;">XXXX</span> -10°C <span style="font-family: monospace;">XXXX</span> +25°C <span style="font-family: monospace;">XX</span>
Measurement range	6.0°C <span style="font-family: monospace;">XXXX</span> -20°C <span style="font-family: monospace;">XXXX</span> +25°C <span style="font-family: monospace;">XX</span>
Measurement range	<span style="font-family: monospace;">XXXXXXXXXXXX</span>
Measurement range	-30 to +80°C
IP rating	<span style="font-family: monospace;">XXXX</span> IP30, <span style="font-family: monospace;">XXXX</span> IP40
LAN	RJ-45 <span style="font-family: monospace;">XXXX</span> 10Base-T <span style="font-family: monospace;">XXXX</span> 100Base-TX
Protocols	WWW, ModbusTCP, SNMPv1, SOAP
Alerts	E-mail ( <span style="font-family: monospace;">XXXX</span> SMTP <span style="font-family: monospace;">XXXX</span> ) <span style="font-family: monospace;">XXXX</span> SNMP Trap <span style="font-family: monospace;">XXXX</span> Syslog
Display	T-Sensor, WWW <span style="font-family: monospace;">XXXX</span>
LCD	<span style="font-family: monospace;">XXXX</span> +70°C <span style="font-family: monospace;">XXXX</span> +70°C <span style="font-family: monospace;">XXXX</span> LCD <span style="font-family: monospace;">XXXX</span>
Thickness	0.025mm - <span style="font-family: monospace;">XXXX</span>
Weight	<span style="font-family: monospace;">XXXX</span> <span style="font-family: monospace;">XXXX</span>
Power	9 to 30Vdc, <span style="font-family: monospace;">XXXX</span> 1W
Dimensions	co-axial, <span style="font-family: monospace;">XXXX</span> 5.5 x 2.1mm
Mounting	G1/2" <span style="font-family: monospace;">XXXX</span>
Height	1m, 2m or 4m <span style="font-family: monospace;">XXXX</span>

□□	88.5 x 93 x 39.5mm (W x H x D), □□□□ 150mm□□□□ 18mm
□□	□□260g - □□1□□□
□□	3□