

# T3611 POE - - kopie - kopie

Model: T3611-4

Temperature line POE

POE 1 2 4

LCD POE IEEE

802.3af



Table

|                       |  |
|-----------------------|--|
| Accuracy              | 0 to 100%  |
| Resolution            | ±2.5% 5 to 95% at 23°C                                       |
| Temperature           | ±0.4°C   |
| Humidity              | 0.1°C, 0.1%RH  |
| Response time         | 2s   |
| Display               | LCD  |
| Power                 | IEEE 802.3af   |
| Operating temperature | ±1.5°C T<25°C RH>30% -60 to +80 °C RH>30% range -60 to +80°C |
| Storage temperature   | -20 to +60°C   |
| IP rating             | IP30, IP40   |
| LAN                   | RJ-45 10Base-T 100Base-TX                                    |
| Protocols             | WWW, ModbusTCP, SNMPv1, SOAP XML                             |
| Alerts                | E-mail (SMTP) SNMP Trap Syslog                               |
| Sensors               | T-Sensor, WWW  |
| Dimensions            | 0.025mm - 18mm   |
| Power                 | POE IEEE 802.3af 5Vdc  |
| Cable                 | co-axial, 5.5 x 2.1mm  |
| Cable length          | 1m, 2m or 4m   |
| Weight                | 136 x 159 x 45mm (W x H x D), 88mm, 18mm                     |
| Weight                | 380g   |
| Warranty              | 3  |