

T7310 - RS232



Model: T7310

Product description

Product description RS232 LCD

Table

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH 5 to 95% at 23°C
Temperature	±0.4°C
Temperature Accuracy	±0.4°C
Temperature Range	±1.5°C (RH < 30%) -60 to +80°C (RH > 30%)
Weight Accuracy	±1.5g/m ³ (T < 25°C) 0 to 400 g/m ³
Weight Accuracy	±2g/kg (T < 35°C) 0 to 550 g/kg
Weight Accuracy	±2g/kg (T < 35°C) 0 to 995 g/kg
Weight Accuracy	±3kJ/kg (T < 25°C) 0 to 995 kJ/kg
Pressure	600 to 1100hPa
Pressure Accuracy	±(1,3hPa+0.06% of reading) at 23°C from 800 to 1100hPa
Pressure Units	hPa, kPa, mbar, mmHg, inHg, inH ₂ O, PSI, oz/in ²
Temperature Range	-30 to +80°C
LCD Display	Monochrome LCD
Protocol	ModBus RTU
Protocol	Advantech ADAM
Protocol	110 to 115200 Bd
Protocol	0.025mm - 0.05mm
IP Rating	IP54, IP40
Power	9-30Vdc, 6mA
Dimensions	88.5 x 170 x 39.5 mm (W x H x D), 75 mm
Weight	230g
Warranty	3 years