

T7311 - RS232 - kopie

Model: T7311-2

Temperature and humidity sensor with RS232 interface and LCD display



Table

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH (5 to 95% at 23°C)
Temperature	±0.4°C
Temperature Accuracy	±0.4°C
Temperature Range	±1.5°C (T < 25°C) RH > 30% -60 to +80°C
Humidity Range	±1.5g/m ³ (T < 25°C) 0 to 400 g/m ³
Humidity Accuracy	±2g/kg (T < 35°C) 0 to 550 g/kg
Humidity Accuracy	±2g/kg (T < 35°C) 0 to 995 g/kg
Humidity Accuracy	±3kJ/kg (T < 25°C) 0 to 995 kJ/kg
Pressure	600 to 1100hPa
Pressure Accuracy	±(1,3hPa+0.06% of reading) at 23°C from 800 to 1100hPa
Pressure Range	hPa, kPa, mbar, mmHg, inHg, inH ₂ O, PSI, oz/in ₂
Temperature Range	-30 to +80°C
LCD Display	Backlight +70°C, LCD
Communication	ModBus RTU, Advantech ADAM
Communication Rate	110 to 115200 Bd
Communication Cable	0.025mm - RS232
IP Rating	IP54, IP40
Power	9-30Vdc, 6mA
Dimensions	1m, 2m or 4m
Dimensions	88.5 x 114 x 39.5 mm (W x H x D), 88 mm, 18mm
Weight	±290g - 1m
Weight	3g