

T7411 - RS485

Model: T7411

Available cable lengths: 1m, 2m, 4m
 RS485 interface: 1, 2, 4 pin LCD display



Table:

| | |
|-----------------------|---|
| Humidity | 0 to 100% |
| Humidity Accuracy | ±2.5% RH (5 to 95% at 23°C) |
| Temperature | ±0.4°C (-30 to +100°C) / ±0.4% RH (+100°C) |
| Temperature Accuracy | ±1.5°C (T < 25°C) / ±0.5°C (-60 to +80°C) |
| Humidity Accuracy | ±1.5g/m ³ (T < 25°C) / ±0.5g/m ³ (0 to 400 g/m ³) |
| Humidity Accuracy | ±2g/kg (T < 35°C) / ±0.5g/kg (0 to 550 g/kg) |
| Humidity Accuracy | ±2g/kg (T < 35°C) / ±0.5g/kg (0 to 995 g/kg) |
| Humidity Accuracy | ±3kJ/kg (T < 25°C) / ±0.5kJ/kg (0 to 995 kJ/kg) |
| Pressure | 600 to 1100hPa |
| Pressure Accuracy | ±(1,3hPa+0.06% of reading) at 23°C from 800 to 1100hPa |
| Pressure Units | hPa, kPa, mbar, mmHg, inHg, inH ₂ O, PSI, oz/in ² |
| Operating Temperature | -30 to +80°C |
| LCD Display | Backlight +70°C, LCD +70°C |
| Protocol | ModBus RTU / Advantech ADAM |
| Rate | 110 to 115200 Bd |
| Dimensions | 0.025mm - 0.001" |
| IP Rating | IP54, IP40 |
| Power | 9-30Vdc, 0.5W |
| Cable Length | 1m, 2m or 4m |
| Dimensions | 88.5 x 114 x 39.5 mm (W x H x D), 88 mm, 18mm |
| Weight | 210g - 1m |
| Material | 3 |