

T7411 - RS485 - kopie - kopie

Model: T7411-4

Available cable lengths: 1m, 2m, 4m
 Available RS485 configurations: 1, 2, 4-wire LCD display



Table:

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH @ 5 to 95% at 23°C
Temperature	±0.4°C @ -30 to +100°C ±0.4% @ +100°C
Temperature Accuracy	±1.5°C @ T < 25°C & RH > 30% ±0.5°C @ -60 to +80°C
Humidity Accuracy	±1.5g/m ³ @ T < 25°C ±0.5g/m ³ @ 0 to 400 g/m ³
Humidity Accuracy	±2g/kg @ T < 35°C ±0.5g/kg @ 0 to 550 g/kg
Humidity Accuracy	±2g/kg @ T < 35°C ±0.5g/kg @ 0 to 995 g/kg
Humidity Accuracy	±3kJ/kg @ T < 25°C ±0.5kJ/kg @ 0 to 995 kJ/kg
Pressure	600 to 1100hPa
Pressure Accuracy	±(1,3hPa+0.06% of reading) at 23°C from 800 to 1100hPa
Pressure Units	hPa, kPa, mbar, mmHg, inHg, inH ₂ O, PSI, oz/in ²
Temperature Range	-30 to +80°C
LCD Display	Backlight +70°C, LCD +70°C, LCD
Protocol	ModBus RTU, Advantech ADAM
Rate	110 to 115200 Bd
Cable Length	0.025mm - 4m
IP Rating	IP54, IP40
Power	9-30Vdc, 0.5W
Cable Length	1m, 2m or 4m
Dimensions	88.5 x 114 x 39.5 mm (W x H x D), 88 mm, 18mm
Weight	210g - 1m
Material	3