

T7511 - 100% Humidity, 100% RH, 100% RH, 100% RH



Model: T7511

100% Humidity, 100% RH, 100% RH, 100% RH

100% Humidity, 100% RH, 100% RH, 100% RH

100% Humidity, 100% RH, 100% RH, 100% RH LCD

100% Humidity, 100% RH, 100% RH, 100% RH

Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

100%

100%	0 to 100%
100%	±2.5% RH 5 to 95% at 23°C
100%	±0.4°C
100%	600 to 1100hPa
100%	±1.3hPa at 23°C
100%	0.1°C, 0.1%RH, 0.1hPa
100%	2s
100%	100%
100%	100%
100%	hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2
100%	±1.5°C RH>30% range -60 to +80 °CRH>30% range -60 to +80°C
100%	100%
100%	-30 to +80°C
IP	IP30, IP40
LAN	RJ-45 10Base-T 100Base-TX
100%	WWW, ModbusTCP, SNMPv1, SOAP
100%	E-mail (SMTP) SNMP Trap Syslog
100%	T-Sensor, WWW
100%	0.025mm - 100%
100%	9-30Vdc, 1W
100%	co-axial, 5.5 x 2.1mm
100%	1m, 2m or 4m
100%	88.5 x 147.5 x 39.5mm (W x H x D), 88mm, 18mm

□□	□□155g-□□1m□□□
□□	3□