

T7511 - kopie

Model: T7511-2

Measurement range: t-line

Measurement range: 1 to 2 to 4



Measurement range: LCD

Measurement range:

Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

Table

Measurement range	0 to 100%
Accuracy	±2.5% (5 to 95% at 23°C)
Resolution	±0.4°C
Measurement range	600 to 1100hPa
Accuracy	±1.3hPa at 23°C
Resolution	0.1°C, 0.1%RH, 0.1hPa
Response time	2s
Measurement range	
Resolution	
Measurement range	hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2
Accuracy	±1.5°C (RH>30% °CRH>30% range -60 to +80°C
Measurement range	
Resolution	
IP rating	IP30, IP40
LAN	RJ-45 10Base-T 100Base-TX
Protocols	WWW, ModbusTCP, SNMPv1, SOAP
Alerts	E-mail (SMTP) SNMP Trap Syslog
Measurement range	T-Sensor, WWW
Measurement range	0.025mm -
Power	9-30Vdc, 1W
Dimensions	co-axial, 5.5 x 2.1mm
Measurement range	1m, 2m or 4m
Dimensions	88.5 x 147.5 x 39.5mm (W x H x D), 88mm, 18mm
Weight	155g-1m
Pages	3