

T7511 - kopie - kopie

Model: T7511-4

Temperature sensor type

Resolution 1/2/4



LCD display

Resolution

Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

Table

Humidity	0 to 100%
Humidity accuracy	±2.5% RH 5 to 95% at 23°C
Temperature	±0.4°C
Pressure	600 to 1100hPa
Pressure accuracy	±1.3hPa at 23°C
Resolution	0.1°C, 0.1%RH, 0.1hPa
Response time	2s
Display	Monochrome
Language	Selectable
Units	hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2
Operating temperature	±1.5°C (RH < 30%) -60 to +80°C (RH > 30%)
Storage temperature	Selectable
Operating range	-30 to +80°C
IP rating	IP30, IP40
LAN	RJ-45 10Base-T / 100Base-TX
Protocols	WWW, ModbusTCP, SNMPv1, SOAP
Alerts	E-mail (SMTP), SNMP Trap, Syslog
Power supply	T-Sensor, WWW
Dimensions	0.025mm - 18mm
Power	9-30Vdc, 1W
Connector	co-axial, 5.5 x 2.1mm
Mounting	1m, 2m or 4m
Weight	88.5 x 147.5 x 39.5mm (W x H x D), 88mm, 18mm

□□	□□155g-□□1m□□□
□□	3□