

# T7611 POE - - kopie



Model: T7611-2

Temperature sensor t-line POE

POE 1 2 4

LCD POE IEEE

802.3af

Table

Humidity	0 to 100%
Humidity Accuracy	±2.5% RH 5 to 95% at 23°C
Temperature	±0.4°C
Pressure	600 to 1100hPa
Pressure Accuracy	±1.3hPa at 23°C
Pressure Units	hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2
Resolution	0.1°C, 0.1%RH, 0.1hPa
Response Time	2s
Power	POE
Power Class	IEEE 802.3af
Operating Temperature	±1.5°C (RH < 30%) -60 to +80°C (RH > 30%)
Storage Temperature	-20 to +60°C
IP Rating	IP30, IP40
LAN	RJ-45 10Base-T 100Base-TX
Protocols	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alerts	E-mail (SMTP), SNMP Trap, Syslog
Sensors	T-Sensor, WWW
Probe	0.025mm - stainless steel
Power	POE IEEE 802.3af 5Vdc
Dimensions	co-axial, 5.5 x 2.1mm
Length	1m, 2m or 4m
Weight	136 x 159 x 45mm (W x H x D), 88mm, 18mm
Weight	380g
Quantity	3