

IoT Wireless Temperature Datalogger for 2 external probes, with built-in GSM modem - kopia - kopia

☐☐: U0121Gsim



GSM Datalogger is designed to record temperature from four external Pt1000 probes. In case of exceeded set limits, SMS and JSON messages can be sent via GPRS data connection. Measured values can be sent to the internet storage [COMET Cloud](#), which is a complete monitoring, alarm and analysis system.

It is also possible to set the regular sending of JSON messages to COMET Database, the sending interval is adjustable. Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper. The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

The device **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard**.

☐☐☐☐

| | |
|---|--|
| Temperature Measuring Range | -200 to +260°C |
| Construction Type | For external temperature probes Pt1000 |
| Accuracy of temperature measurement | ±0.2°C; ±0,2 % of the measurement value in a range of +100 to +260 °C |
| Resolution of the reading | 0.1°C |
| Response time t90 of temperature measurement (temperature step 20°C, air flow approximately 1m/s) | According to the connected probe |
| Real time clock | Year, leap year, month, day, hour, minute, second |
| Data logging interval | Adjustable from 1s to 24h |
| Display and alarm refresh | Adjustable 1s, 10s, 1min |
| Total memory capacity | 500 000 values in noncyclic logging mode, 350 000 values in cyclic record mode |
| Data logging mode | Noncyclic - data logging stops after filling the memory, cyclic - after filling memory oldest data is overwritten by new |
| Power | Battery SONY Lilon 5200mAh |
| IP protection | IP67 - protected against influence of temporary immersion into water |
| Dimensions | 61x93x53, with antenna 120x93x53 |
| Weight including battery | 270 g |
| Warranty | 3 years |