

WiFi temperature and relative humidity sensor for external probe

□□: W3711



Sensors with WiFi interface are designed to measure the temperature and relative humidity with a connected probe (optional accessories).

Communication with the sensor is done via a wireless WiFi network. The device allows sending measured values to the online [COMET Cloud](#) or [COMET Database](#) storage with the shortest interval of 5 minutes. The values can be displayed on integrated web pages and provided to third party systems using the Modbus TCP protocol. The measured values are displayed on the LCD display.

The device continuously evaluates the alarm limits of the measured values and in case of exceeding them, it can send an e-mail or inform by means of acoustic or optical signaling. Two alarm limits are supported for each measurement channel.

The main advantage of sensors with WiFi interface is the simplicity of deployment in places where WiFi infrastructure is already available. Just place the sensor in the desired location and connect it to the WiFi network. WiFi sensor in conjunction with [COMET Cloud](#) or [COMET Database](#) offers a comprehensive solution for monitoring and alarm without the need for a server solution on the part of the user. If necessary, however, the sensor can also be connected to third-party systems, either using the Modbus TCP protocol or by sending JSON data to an http server.

Thanks to these unique features, the WiFi sensor will find applications and a wide range of application areas.

□□□□

TEMPERATURE SENSOR	
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	0.1% RH
DEW POINT	
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	according to the connected probe Digi/E
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +60 °C
Channels	1x connectable temperature+humidity probe, ELKA connector
Measuring interval	1 s

Sending interval to COMET Cloud	adjustable 5 minutes to 12 hours
Communication protocols	HTTP(S), SMTP, ModbusTCP, HTTP POST
Alarm signalization	e-mail, acoustic, LED
Power	5.0 to 5.4 VDC; consumption 300 mA (max. 500 mA); USB-C connector
Radio section	frequency: 2.4 GHz; max. transmit power: 18 dBm; standard: 802.11 b/g/n; contain CC3220MODSF with FCC ID: Z64-CC3220MOD
Protection class	IP30
Dimensions	81 x 93 x 32 mm
Weight	115 g
Warranty	3 years